

10serisi / ten series / Technical Specifications

10x8

	SAT	TERR
Frequency Range	950-2150 Mhz	47-870 Mhz
Connection Gain	+2dB ±1	-1dB ±1
Cascade Loss	-1dB ±2	-3dB ±1
Output Level	(IMA 3) 102dBµV	
Total Current Draw With LNB	650 mA (18V DC)	
Decoupling SAT/TERR	> 36 dB	
Decoupling SAT/SAT	> 34 dB	
Decoupling Subscriber / Subscriber	> 34 dB	

10x16

	SAT	TERR
Frequency Range	950-2150 Mhz	47-870 Mhz
Connection Gain	+3dB ±1	-3dB ±1
Cascade Loss	-2dB ±2	-4dB ±1
Output Level	(IMA 3) 102dBµV	
Total Current Draw With LNB	650 mA (18V DC)	
Decoupling SAT/TERR	> 37 dB	
Decoupling SAT/SAT	> 34 dB	
Decoupling Subscriber / Subscriber	> 34 dB	

10x24

	SAT	TERR
Frequency Range	950-2150 Mhz	47-870 Mhz
Connection Gain	+2dB ±1	-1dB ±1
Cascade Loss	-4dB ±2	-4dB ±1
Output Level	(IMA 3) 102dBµV	
Total Current Draw With LNB	800 mA (18V DC)	
Decoupling SAT/TERR	> 38 dB	
Decoupling SAT/SAT	> 34 dB	
Decoupling Subscriber / Subscriber	> 34 dB	

10x12

	SAT	TERR
Frequency Range	950-2150 Mhz	47-870 Mhz
Connection Gain	+3dB ±1	-2dB ±1
Cascade Loss	-2dB ±2	-3dB ±1
Output Level	(IMA 3) 102dBµV	
Total Current Draw With LNB	650 mA (18V DC)	
Decoupling SAT/TERR	> 35 dB	
Decoupling SAT/SAT	> 33 dB	
Decoupling Subscriber / Subscriber	> 34 dB	

10x20

	SAT	TERR
Frequency Range	950-2150 Mhz	47-870 Mhz
Connection Gain	+2dB ±1	-3dB ±1
Cascade Loss	-3dB ±2	-4dB ±1
Output Level	(IMA 3) 102dBµV	
Total Current Draw With LNB	650 mA (18V DC)	
Decoupling SAT/TERR	> 37 dB	
Decoupling SAT/SAT	> 34 dB	
Decoupling Subscriber / Subscriber	> 34 dB	

10x32

	SAT	TERR
Frequency Range	950-2150 Mhz	47-870 Mhz
Connection Gain	+1dB ±1	-7dB ±1
Cascade Loss	-5dB ±2	-4dB ±1
Output Level	(IMA 3) 102dBµV	
Total Current Draw With LNB	800 mA (18V DC)	
Decoupling SAT/TERR	> 37 dB	
Decoupling SAT/SAT	> 33 dB	
Decoupling Subscriber / Subscriber	> 34 dB	



Professional high-quality satellite multiswitches



TEKNO LINE®

ZinkKasa *profesyonel seri* Multiswitch

ten series



profesyonel
MULTISWITCH

10 serisi / Product Range Ürün Yelpazesi

TPS 10x8 S/K - TPS 10x12 S/K - TPS 10x16 S/K
TPS 10x20 S/K - TPS 10x24 S/K - TPS 10x32 S/K



tekniksatsat
GROUP

www.tekniksatsatgroup.com.tr
www.tekno line.net

10 GİRİŞ 3 UYDU MERKEZİ YAYIN DAĞITIM SANTRALİ MULTISWITCH

- Terrestrial girişinden aktif kazanç devresi
- 100 volt'a kadar abone port koruması
- Abone başına 100 mt. dağıtım uzunluğu
- LED'li abone kontrol sistemi
- Ergonomik ve şık tasarım
- Karasal digital yayınlara uyumlu
- DISEqC 2.0 yazılım sayesinde uydu alıcısı seçmez
- Yüksek abone dağıtımlarında düşük kaskat kaybı
- Sıfır port arzansı
- SMPS güç kaynağı
- Yüksek izolasyon sayesinde düşük sinyalde çalışabilme
- Kolay kurulum
- Yeni nesil komponentler sayesinde düşük güç kullanımı
- -20dB Ayar imkanı

